

# T2QuickNet Mat



**RAYCHEM**

## UNDERFLOOR HEATING PRODUCT LIST



### T2QuickNet 90 w/m<sup>2</sup> for use on a timber subfloor

#### Wattage/Power

|                                      |      |
|--------------------------------------|------|
| T2QuickNet 1 m <sup>2</sup> Timber   | 90   |
| T2QuickNet 1.5 m <sup>2</sup> Timber | 135  |
| T2QuickNet 2 m <sup>2</sup> Timber   | 180  |
| T2QuickNet 2.5 m <sup>2</sup> Timber | 225  |
| T2QuickNet 3 m <sup>2</sup> Timber   | 275  |
| T2QuickNet 3.5 m <sup>2</sup> Timber | 315  |
| T2QuickNet 4 m <sup>2</sup> Timber   | 360  |
| T2QuickNet 4.5 m <sup>2</sup> Timber | 405  |
| T2QuickNet 5 m <sup>2</sup> Timber   | 450  |
| T2QuickNet 6 m <sup>2</sup> Timber   | 545  |
| T2QuickNet 7 m <sup>2</sup> Timber   | 630  |
| T2QuickNet 8 m <sup>2</sup> Timber   | 725  |
| T2QuickNet 9 m <sup>2</sup> Timber   | 800  |
| T2QuickNet 10 m <sup>2</sup> Timber  | 915  |
| T2QuickNet 12 m <sup>2</sup> Timber  | 1100 |

\*N.B Thermostats can switch up to 33 m<sup>2</sup> of T2QuickNet for Timber - any larger requires an additional thermostat or electrician to supply a contactor

### T2QuickNet 160 w/m<sup>2</sup> for use on Concrete subfloors or Isolecta insulation boards

#### Wattage/Power

|                                        |      |
|----------------------------------------|------|
| T2QuickNet 1 m <sup>2</sup> Concrete   | 160  |
| T2QuickNet 1.5 m <sup>2</sup> Concrete | 240  |
| T2QuickNet 2 m <sup>2</sup> Concrete   | 320  |
| T2QuickNet 2.5 m <sup>2</sup> Concrete | 400  |
| T2QuickNet 3 m <sup>2</sup> Concrete   | 480  |
| T2QuickNet 3.5 m <sup>2</sup> Concrete | 560  |
| T2QuickNet 4 m <sup>2</sup> Concrete   | 640  |
| T2QuickNet 4.5 m <sup>2</sup> Concrete | 720  |
| T2QuickNet 5 m <sup>2</sup> Concrete   | 800  |
| T2QuickNet 6 m <sup>2</sup> Concrete   | 960  |
| T2QuickNet 7 m <sup>2</sup> Concrete   | 1120 |
| T2QuickNet 8 m <sup>2</sup> Concrete   | 1280 |
| T2QuickNet 9 m <sup>2</sup> Concrete   | 1440 |
| T2QuickNet 10 m <sup>2</sup> Concrete  | 1600 |

\*N.B Thermostats can switch up to 18 m<sup>2</sup> of T2QuickNet for Concrete - any larger requires an additional thermostat or electrician to supply a contactor



## UNDERFLOOR HEATING PRODUCT LIST

### CeraPro Loose Cable

|                                   | Length of Cable           | Coverage on Concrete/Isolecta<br>(75 mm spacing) | Coverage on Timber<br>(110 mm spacing) |
|-----------------------------------|---------------------------|--------------------------------------------------|----------------------------------------|
| 160 W CeraPro                     | 14 m                      | 1 m <sup>2</sup>                                 | 1.5 m <sup>2</sup>                     |
| 240 W CeraPro                     | 28 m                      | 1.5 m <sup>2</sup>                               | 2.5 m <sup>2</sup>                     |
| 320 W CeraPro                     | 28 m                      | 2 m <sup>2</sup>                                 | 3 m <sup>2</sup>                       |
| 400 W CeraPro                     | 35 m                      | 2.5 m <sup>2</sup>                               | 4 m <sup>2</sup>                       |
| 475 W CeraPro                     | 43 m                      | 3 m <sup>2</sup>                                 | 4.5 m <sup>2</sup>                     |
| 635 W CeraPro                     | 57 m                      | 4 m <sup>2</sup>                                 | 6 m <sup>2</sup>                       |
| 800 W CeraPro                     | 71 m                      | 5 m <sup>2</sup>                                 | 7.5 m <sup>2</sup>                     |
| 1140 W CeraPro                    | 100 m                     | 7.5 m <sup>2</sup>                               | 11 m <sup>2</sup>                      |
| Splice Kit for T2QuickNet/CeraPro | Repair and extension kits |                                                  |                                        |

\*N.B. Thermostats can switch up to 3000 W of CeraPro - greater than this size will require an additional thermostat or electrician to supply a contactor.

### Isolecta Insulation Boards

|                                         | Details                                                 | Coverage                     |
|-----------------------------------------|---------------------------------------------------------|------------------------------|
| Isolecta Insulation boards              | 1 pk= 4 boards 10 mm                                    | 2.85 m <sup>2</sup> area     |
| Net Band (Jointing tape)                | 25 m x 125 mm                                           | Approximately 2 pks Isolecta |
| Fixing pins for concrete subfloors      | Fixing pins for concrete subfloors - 35 pcs per box     | 1 pk Isolecta                |
| Washers and screws for wooden subfloors | Washer and screws for wooden subfloors - 35 pcs per box | 1 pk Isolecta                |

### Thermostats

NRG-DM digital programmable thermostat

White as standard

Green Leaf touchscreen thermostat

Green Leaf touchscreen thermostat-Black mirrored screen with chrome trim

### United Kingdom

Tel 0800 969 013

Fax 0800 968 624

salesthermalUK@nvent.com



nVent.com

Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**